



SO250

Name: **Tension clamp**
 IMWS 50-70 mm² (with bracket)


Type: SO250

GTIN: 6418677418679

Description: For tensioning of LV ABC cables in an insulated messenger wire systems (IMWS). Clamp is equipped with bracket for easy installation in every climatic conditions.

Package: 10/540

Unit: PCS



Technical specification

Mechanical

SMFL 15 kN

Dimensions

Weight 0.580 kg
 Messenger diameter 11 ... 14 mm
 Messenger conductor size 50 ... 70 mm²

Features

Includes bracket x

Use: Tension clamp with bracket for anchoring insulated messenger wire system.

Construction:	Component	Material
	Body	Corrosion resistant aluminium alloy
	Wedges and other plastic parts	UV resistant plastic
	Bail	Stainless steel A2
	Bracket	Corrosion resistant aluminium alloy

Installation: Wedges are opened and messenger is installed between wedges. Then wedges are pushed back to tighten them on messenger.
 When needed, bail can be opened by moving one of end pieces about 10 cm out of the clamp. After installing the bail through bracket must both aluminium pieces on the bail be assembled back inside the groove.

Tools required: No tools required.

Markings: SO 250, Ensto, 50-70 mm², PA 1500



Saves Your Energy

PRODUCT SPECIFICATION

11.9.2015

2/2

SO250

Standard:

NF C 33-041

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2770

www.ensto.com