



# SO252

Name: **Tension clamp**  
 IMWS 25-35 mm<sup>2</sup> (with bracket)

Type: SO252

GTIN: 6418677418716

Description: For tensioning of LV ABC cables in an insulated messenger wire systems (IMWS). Clamp is equipped with bracket for easy installation in every climatic conditions.

Package: 10/540

Unit: PCS



## Technical specification

### Mechanical

SMFL 12 kN

### Dimensions

Weight 0.58 kg

Messenger diameter 8.5 ... 11 mm

Messenger conductor size 25 ... 35 mm<sup>2</sup>

### Features

Includes bracket x

Use: Tension clamp with bracket for anchoring insulated messenger wire system.

Construction:	Component	Material
	Body	Corrosion resistant aluminium alloy
	Wedges+other plastic parts	UV resistant plastic
	Bail	Stainless steel A2
	Bracket	Corrosion resistant aluminium alloy

Installation: Wedges are opened and messenger is installed between wedges. Then wedges are pushed back to tighten them on messenger. When needed bail can be opened by moving one of the end pieces about 10 cm out of the clamp. After installing the bail through bracket must both aluminium pieces on the bail be assembled back inside the groove.

Tools required: No tools required.

Markings: SO 252, 25-35 mm<sup>2</sup>, EA 1500



*Saves Your Energy*

## PRODUCT SPECIFICATION

11.9.2015

2/2

# SO252

Standard:

NF C 33-041

---

Ensto Finland Oy

Ensio Miettisen katu 2  
P.O.Box 77  
06101 Porvoo, Finland

Tel. +358 204 76 21  
Fax +358 204 76 2770

[www.ensto.com](http://www.ensto.com)