



Saves Your Energy

PRODUCT SPECIFICATION

18.10.2015

1/2



SLJ1.27

Name: **Connector with shear head bolts**

Al/Cu 6-50 mm² 2 bolts

Type: SLJ1.27

GTIN: 6418677458187


Description: The connectors are used for jointing conductors of up to 1 kV cables. Because of the shear head bolt construction no crimping tools are needed. The required torque is achieved by tightening the bolt until it breaks off. The connectors are longitudinally water tight and they are suitable both for aluminium and copper conductors, solid and stranded, sector shaped and circular. The core insulation may be as well plastic as paper.



Photo presented is indicative only

Package: 100/7000

Unit: PCS



Technical specification

Ratings

ETIM class Connector to screw

Dimensions

Weight 0.034 kg

Conductor size Al/Cu 6-50

Drawing markings

d 11 mm

D 20 mm

L1 26 mm

L2 54 mm

ETIM

Nominal cross section copper, RM 6 ... 50 mm²

Nominal cross section copper, RE 6 ... 50 mm²

Nominal cross section copper, SM 6 ... 50 mm²

Nominal cross section aluminium, RM 6 ... 50 mm²

Nominal cross section aluminium, RE 6 ... 50 mm²

Nominal cross section aluminium, SM 6 ... 50 mm²

Nominal cross section aluminium, SE 6 ... 50 mm²

Material conductor Aluminium/copper

Surface protection Tinned

Oil stop/centre bar x

Insulation



Saves Your Energy

PRODUCT SPECIFICATION

18.10.2015

2/2



SLJ1.27

Use:	The connectors are used for jointing conductors of up to 1 kV cables. The connectors are longitudinally water tight and they are suitable both for aluminium and copper conductors, solid and stranded, sector shaped and circular.
Construction:	Body: tinned aluminium alloy, tin layer thickness >12µm Screws: tinned aluminium alloy Grease: RFL3
Installation:	<ul style="list-style-type: none">- Remove insulation- Brush the conductor- Insert cables inside the connector- Tighten screws from both sides a bit starting from the screw nearest insulation. Then continue tightening until screws break.
Tools required:	SW 11 wrench
Markings:	Ensto ww/yyyy SLJ1.27 Al/Cu 6-50mm ² Class A
Standard:	IEC 61238-1