



Saves Your Energy

PRODUCT CARD

22.10.2015

Rapid5.3/411

Name: **Ensto Rapid**
green, RAL7008


Type: Rapid5.3/411

GTIN: 6438100315054

Description: Ensto Rapid 5.3/411 is a pre-installed distribution cabinet with connectors and fuses all in the same package.

Package: 1/5

Unit: PCS



Technical specification

Electrical values

Fuse max. 3 x 160 A

Short-circuit characteristics

Rated short time withstand current <10 kA

Ratings

Rated voltage 400 V

Rated frequency 50 Hz

Rated current 250 A

Dimensions

Height 850 mm

Width 610 mm

Depth 210 mm

Weight 56.5 kg

Main conductor 2 x 35-240 mm²

Branch conductor 2 x 35-240 / 4 x 6-50 / 4 x 6-50 mm²

Features

Lock type Triangle lock

Materials

Material Galvanized steel

Surface treatment Polyester powder coating

Colors

Color Green

Color code RAL7008

Certificates

Standards EN 61439-1, EN 61439-5

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2770

www.ensto.com