



Saves Your Energy

PRODUCT CARD

7.10.2015

COT1.4202L

Name:	Outdoor coldshrink termination 20,8/36 (42) kV Al/Cu 10-95 mm ² 3x1 core with lugs
Type:	COT1.4202L
GTIN:	6438100304874
Description:	The termination kit is used for outdoor terminating of max. 42 kV cables with XLPE insulation and copper wire shield. The kit is suitable for single core cables, containing the components for three cores. The kit includes the shear head bolt cable lugs suitable both for aluminium and copper conductors, and all the components needed for terminating: shear head bolt cable lugs for the cable wire shield, mastics, tapes, cleaning and grinding materials, insulating anti-tracking tubes with sheds.
Package:	0/1/54
Unit:	PCS



Photo presented is indicative only

Technical specification

Dimensions

Conductor size 36 kV	Al/Cu 10-95
Conductor size 42 kV	Al/Cu 10-95
Termination length L	620 mm
Creepage distance	980 mm
Diameter on the insulation	≥ 18.4 mm
Spiral inner diam.	50 mm
Max. application diam.	≤ 36 mm
Shed diameter	100 mm

Temperatures

Min. installation temperature	-25 °C
Operating temperature	-50 ... 65 °C

Features

Connectors	Ø max 36 mm
No of sheds per phase	6

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2770

www.ensto.com