



Saves Your Energy

PRODUCT CARD

7.10.2015

# COT1.4204L

Name: **Outdoor coldshrink termination**  
20,8/36 (42) kV Al/Cu 150-300 mm<sup>2</sup> 3x1 core with lugs

Type: COT1.4204L

GTIN: 6438100304881

Description: The termination kit is used for outdoor terminating of max. 42 kV cables with XLPE insulation and copper wire shield. The kit is suitable for single core cables, containing the components for three cores.

The kit includes the shear head bolt cable lugs suitable both for aluminium and copper conductors, and all the components needed for terminating: shear head bolt cable lugs for the cable wire shield, mastics, tapes and cold shrink termination tubes

Package: 0/1/54

Unit: PCS



Photo presented is indicative only

## Technical specification

### Dimensions

Conductor size 36 kV	Al/Cu 185-300
Conductor size 42 kV	Al/Cu 185-300
Termination length L	800 mm
Creepage distance	1100 mm
Diameter on the insulation	≥ 31.1 mm
Spiral inner diam.	70 mm
Max. application diam.	≤ 61 mm
Shed diameter	100 mm

### Temperatures

Min. installation temperature	-25 °C
Operating temperature	-50 ... 65 °C

### Features

Connectors	Ø max 60 mm
No of sheds per phase	6

Ensto Finland Oy

Ensio Miettisen katu 2  
P.O.Box 77  
06101 Porvoo, Finland

Tel. +358 204 76 21  
Fax +358 204 76 2770

[www.ensto.com](http://www.ensto.com)