



SAL2.27

Name: **Cable lug with shear head bolts**

Al/Cu 50-95 mm² ø 10.5 mm

Type: SAL2.27

GTIN: 6418677401442


Description: The cable lugs are used for terminating conductors of up to 1 kV cables. Because of the shear head bolt construction no crimping tools are needed. The required torque is achieved by tightening the bolt until it breaks off. The lugs are longitudinally water tight and they are suitable both for aluminium and copper conductors, solid and stranded, sector shaped and circular.

Package: 100/6300

Unit: PCS



Photo presented is indicative only



Technical specification

Ratings

ETIM class Screw cable lug

Dimensions

Weight 0.078 kg

Conductor size Al/Cu 50-95

Drawing markings

B	25 mm
d	14.5 mm
D1	25 mm
D2	10.5 mm
H	7 mm
L1	50 mm
L2	73 mm
L3	86 mm
SW	14 mm

ETIM

Nominal cross section copper, RM	50 ... 95 mm ²
Nominal cross section copper, RE	50 ... 95 mm ²
Nominal cross section copper, SM	50 ... 95 mm ²
Nominal cross section aluminium, RM	50 ... 95 mm ²
Nominal cross section aluminium, RE	50 ... 95 mm ²
Nominal cross section aluminium, SM	50 ... 95 mm ²
Nominal cross section aluminium, SE	50 ... 95 mm ²
Material conductor	Aluminium/copper
Surface protection	Tinned



Saves Your Energy

PRODUCT CARD

18.10.2015

2/2

SAL2.27

With shear-off head

x

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2770

www.ensto.com