



Saves Your Energy

PRODUCT CARD

18.10.2015

SLJ1.27

Name: **Connector with shear head bolts**

Al/Cu 6-50 mm² 2 bolts

Type: SLJ1.27

GTIN: 6418677458187


Description: The connectors are used for jointing conductors of up to 1 kV cables. Because of the shear head bolt construction no crimping tools are needed. The required torque is achieved by tightening the bolt until it breaks off. The connectors are longitudinally water tight and they are suitable both for aluminium and copper conductors, solid and stranded, sector shaped and circular. The core insulation may be as well plastic as paper.



Photo presented is indicative only

Package: 100/7000

Unit: PCS



Technical specification

Ratings

ETIM class Connector to screw

Dimensions

Weight 0.034 kg

Conductor size Al/Cu 6-50

Drawing markings

d 11 mm

D 20 mm

L1 26 mm

L2 54 mm

ETIM

Nominal cross section copper, RM 6 ... 50 mm²

Nominal cross section copper, RE 6 ... 50 mm²

Nominal cross section copper, SM 6 ... 50 mm²

Nominal cross section aluminium, RM 6 ... 50 mm²

Nominal cross section aluminium, RE 6 ... 50 mm²

Nominal cross section aluminium, SM 6 ... 50 mm²

Nominal cross section aluminium, SE 6 ... 50 mm²

Material conductor Aluminium/copper

Surface protection Tinned

Oil stop/centre bar x

Insulation

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2770

www.ensto.com