



Saves Your Energy

PRODUCT CARD

18.10.2015

SLJ3.47

Name: **Connector with shear head bolts**

Al/Cu 95-240 mm² 4 bolts

Type: SLJ3.47

GTIN: 6418677459726


Description: The connectors are used for jointing conductors of up to 1 kV cables. Because of the shear head bolt construction no crimping tools are needed. The required torque is achieved by tightening the bolt until it breaks off. The connectors are longitudinally water tight and they are suitable both for aluminium and copper conductors, solid and stranded, sector shaped and circular. The core insulation may be as well plastic as paper.



Photo presented is indicative only

Package: 50/2700

Unit: PCS



Technical specification

Ratings

ETIM class Connector to screw

Dimensions

Weight 0.278 kg

Conductor size Al/Cu 95-240

Drawing markings

d 25.5 mm

D 37.7 mm

L1 58 mm

L2 119 mm

ETIM

Nominal cross section copper, RM 95 ... 240 mm²

Nominal cross section copper, RE 95 ... 240 mm²

Nominal cross section copper, SM 95 ... 240 mm²

Nominal cross section aluminium, RM 95 ... 240 mm²

Nominal cross section aluminium, RE 95 ... 240 mm²

Nominal cross section aluminium, SM 95 ... 240 mm²

Nominal cross section aluminium, SE 95 ... 240 mm²

Material conductor Aluminium/copper

Surface protection Tinned

Oil stop/centre bar x

Insulation

Ensto Finland Oy

Ensio Miettisen katu 2
P.O.Box 77
06101 Porvoo, Finland

Tel. +358 204 76 21
Fax +358 204 76 2770

www.ensto.com